

Wall mounted unit

Attractive, wall mounted design with perfect indoor air quality

- › Seasonal efficiency values up to A+++ in cooling and heating thanks to its up-to-date technology and built-in intelligence
- › Practically inaudible: the unit runs so quietly, you will almost forget it is there
- › Fresher, cleaner air thanks to Daikin's Flash Streamer technology: you can breathe deep with no worries about impure air
- › 2-area intelligent eye: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-efficient setting
- › 3D air flow combines vertical and horizontal auto-swing to circulate a stream of warm or cool air right to the corners of even large spaces
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Sleek, unobtrusive air conditioning unit that matches European sensibilities regarding interior design
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency



Indoor Units			FTXM20M	FTXM25M	FTXM35M	FTXM42M	FTXM50M	FTXM60M	FTXM71M
Capacity	UK Total Cooling	kW	1.95	2.44	3.42	4.11	4.56	TBC	TBC
	UK Sensible Cooling	kW	1.65	1.82	2.56	2.85	3.14	TBC	TBC
	Nominal Cooling	kW	2.00	2.50	3.50	4.20	5.00	6.0	7.1
	Nominal Heating	kW	2.50	3.40	4.00	5.40	5.80	7.0	8.2
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+++	A+++	A+++	A++	A++	A++	A++
	Pdesign	kW	2.00	2.50	3.40	4.20	5.00	6	6.8
	SEER		8.53	8.52	8.51	7.50	7.33	6.9	6.11
	Annual Energy Consumption	kWh	83	103	140	196	239	304	390
Seasonal Efficiency (EN14825) HEATING	Energy Label		A+++	A+++	A+++	A++	A++	A+	A
	Pdesign	kW	2.30	2.40	2.50	4.00	4.60	4.6	6.2
	SCOP		5.10	5.10	5.10	4.60	4.60	TBC	TBC
	Annual Energy Consumption	kWh	632	659	686	1217	1400	1498	2278
Nominal Efficiency	Energy Label		A / A	A / A	A / A	A / A	A / A	A / A	B / D
	EER / COP		4.57 / 5.00	4.50 / 5.00	4.23 / 4.04	3.75 / 4.12	3.68 / 4.00	3.39 / 3.61	3.03 / 3.19
	Annual Energy Consumption	kWh	219	278	402	560	682	885	1174
Air Flow Rate	High / Low / Silent	m³/sec	0.185 / 0.100 / 0.073	0.185 / 0.103 / 0.073	0.210 / 0.106 / 0.076	0.210 / 0.118 / 0.076	0.266 / 0.185 / 0.168	- / 0.318 / -	- / 0.341 / -
Dimensions	Height	mm	272	272	272	272	295		
	Width	mm	811	811	811	811	1040		
	Depth	mm	294	294	294	294	300		
Weight		kg	10	10	10	10	14.5		
Sound Pressure	High / Low / Silent	dBA	41 / 25 / 19	41 / 25 / 19	45 / 29 / 19	45 / 30 / 21	46 / 37 / 34	TBC	TBC
Sound Power		dBA	57	57	60	60	60	61	62

Outdoor Units			RXM20M	RXM25M	RXM35M	RXM42M	RXM50M	RXM60M	RXM71M
Dimensions	Height x Width x Depth	mm	550 x 765 x 285				735 x 825 x 300		735 x 870 x 320
Weight		kg	32	32	32	44	44	44	44
Electrical Details	Power Supply		1ph				1ph		
	Running Current	A	1.95	2.47	4.23	4.97	6.48	TBC	TBC
	Starting Current	A	3.7	3.7	4.4	6.8	6.6	TBC	TBC
	Max Fuse Size	A	10	10	10	20	20	TBC	TBC
Interconnection Wiring	Core / Cable size		3+E / 1.5				3+E / 2.5		TBC
Piping Connections	Liquid / Gas	inches	1/4 (6.4) / 3/8 (9.5)				1/4 (6.4) / 1/2 (12.7)		TBC
Pipework	Maximum Length	m	20	20	20	30	30	30	30
	Maximum Vertical Rise	m	15	15	15	15	15	15	15
	Precharged to	m	10	10	10	10	10	10	10
	Additional Charge	g/m	20				20		
	Holding Charge	kg	0.76	0.76	0.76	1.30	1.4	1.5	1.7
Sound Pressure	High / Silent	dBA	46 / -	46 / -	49 / -	48 / 44	48 / 44	48 / 44	47 / -
Sound Power		dBA	59	59	61	63	63	63	66
Air Flow Rate (Cooling)	High	m³/sec	0.600	0.600	0.600	0.848	0.840	TBC	TBC
ECA Eligible			●	●	●	●	●	●	●