MENDIP

double pantile design with elegant wing lines, providing instant visual appeal.



OLOUR AVAILABILITY















Key
(G) Granular finish
(S) Smooth finish

CHNICAL DATA

e of tile	420mm x 330mm	
imum pitch*	17.5° Smooth (75mm headlap) 15° Smooth (100mm headlap)	30° Granular (75mm headlap) 25° Granular (100mm headlap)
ximum pitch	90°	
imum headlap	75mm	
ximum gauge	345mm	
ly thickness	27mm (nominal)	
erall depth	59mm	
er width	298mm (nominal)	
nging length	397mm (nominal)	
vering capacity (net)	9.7 tiles/m² at 75mm headlap	10.5 tiles/m² at 100mm headlap
ght of tiling (approx.)	46kg/m² (0.45 kN/m²) at 75mm headlap	49kg/m² (0.48 kN/m²) at 100mm headlap
tens required (net)	2.9 lin.m/m² at 75mm headlap	3.1 lin.m/m² at 100mm headlap
ten size recommended	38mm x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534) 50mm x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534)	
nails	70mm x 3.35mm	
ng clips	Eaves, verge and tile clips	
hority	BS EN 490	

e minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.

JSTAINABILITY

A+ rated in the BRE Green Guide (based on generic rating for UK produced concrete interlocking tiles Element Refs: 812410007, 812410018, 812410049)

BES 6001 Responsible Sourcing certified

EXTENDED RAFTER LENGTHS

Mendip interlocking tiles can now perform at extended rafter lengths as follows:

- 15° - 17.5° pitch with a rafter length up to and including 15m will require a 100mm headlap.
- 17.5° pitch and above with a rafter length up to and including 15m will require a 75mm headlap.

MENDIP 12.5

lowpitch

A double pantile designed with a variable gauge and subtle design modifications to achieve an even lower pitch.



COLOUR AVAILABILITY







Key
(S) Smooth finish

TECHNICAL DATA

Size of tile	420mm x 330mm
Minimum pitch*	12.5° Smooth (100mm headlap, up to 6m rafters)
Maximum pitch**	44°
Minimum headlap	100mm
Maximum gauge	320mm
Body thickness	27mm (nominal)
Overall depth	59mm
Cover width	298mm (nominal)
Hanging length	397mm (nominal)
Covering capacity (net)	10.5 tiles/m² at 100mm headlap
Weight of tiling (approx.)	49kg/m² (0.48 kN/m²) at 100mm headlap
Battens required (net)	3.1 lin.m/m² at 100mm headlap
Batten size recommended	38mm x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534) 50mm x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534)
Fixing clips	Eaves, verge and tile clips, Mendip headclip, SoloFix
Authority	BS EN 490

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.

** For rafter pitches over 15°, see Mendip (page 38).

SUSTAINABILITY

- ✓ A+ rated in the BRE Green Guide (based on generic rating for UK produced concrete interlocking tiles Element Refs: 812410007, 812410018, 812410049)
- ✓ BES 6001 Responsible Sourcing certified