

Isaro Pro

IP 24L35 727 NR BP 3550 CL1 M76 GY-S

THORN




Isaro Pro

A state of the art LED road lighting lantern (small) with 24 LEDs driven at 350mA with Narrow Road optic. Programmable LED driver. Class I electrical, IP66, IK09. Housing: die-cast aluminium (EN AC-44300), powder coated textured Light grey textured (150) - partly painted. Spigot: die-cast aluminium (EN AC-44300), unpainted. Enclosure: 5mm thick glass. Fixings: stainless steel. Supplied with Ø76mm spigot adaptor which can be fitted for post-top (0°/5°/10°/15°/20° tilt) or side-entry (-15°/-10°/-5°/0°/5°/10°/15° tilt). BPxyz: Autonomous bi-power reduction (x: hours before midnight, y: hours after midnight, zz: reduction (%)) Complete with 2700K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.


Dimensions: 571 x 224 x 114 mm
 Luminaire input power: 25.7 W
 Luminaire luminous flux: 3542 lm
 Luminaire efficacy: 138 lm/W
 Weight: 5.7 kg
 Scx: 0.054 m²



TLG_ISRP_F_PDB_SIL.jpg



TLG_ISRP_M_LD1.wmf



Light Source: LED
 Luminaire luminous flux*: 3542 lm
 Luminaire efficacy*: 138 lm/W
 Colour Rendering Index min.: 70
 Ballast: 1 x 87500878 LCO 60/200-1050/100 NF C
 ADV3

Correlated colour temperature*: 2700 Kelvin
 Chromaticity tolerance (initial MacAdam): 5
 Rated useful life (B10)*: L95 100000h at 25°C
 Luminaire input power*: 25.7 W Power factor = 0.85
 Dimming: PROG
 LOR: 1,00 ULOR: 0,00 DLOR: 1,00

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
 © Thorn Lighting