

Piazza II LED

THORN

PIAZZA II LED 1690-827 HF ANT

LED 15W TL_PIA2-827	ida DALI DIM APPROVED	IP65	IK10	⏏	CE	⚡	☀	⊗	⊙	T _a -20 +40	
---------------------	--------------------------	------	------	---	----	---	---	---	---	---------------------------	--

Piazza II LED

A robust Wall mounted luminaire. Electronic, fixed output control gear. Back plate: die-cast aluminium, painted anthracite. Body: anthracite polycarbonate. Ø20mm cable entry via rear or side conduit entries, BESA compatible. IP65, IK10. Complete with 2700K LED.

Dimensions: 381 x 196 x 305 mm

Luminaire input power: 15.1 W


Luminaire luminous flux: 1815 lm

Luminaire efficacy: 120 lm/W


Weight: 2.8 kg



TLG_PIA2_F_PDB.jpg



TLG_PIA2_M_LD1.wmf



D43175AA.ltd

Lamp position: STD - standard

Light Source: LED

Luminaire luminous flux*: 1815 lm

Luminaire efficacy*: 120 lm/W

Colour Rendering Index min.: 80

Correlated colour temperature*: 2700 Kelvin

Chromaticity tolerance (initial MacAdam): 5

Rated median useful life*:

L70 60000 h at 25 °C

Ballast: 1x HF_

Luminaire input power*: 15.1 W

Dimming: FO

LOR: 1,00 ULOR: 0,02 DLOR: 0,98

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting