



BL03

Straight to mains Iroko wood

FEATURES

IP rating	IP65
IK rating	Other
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	5500g
Inrush Current	60A 0.037ms
Construction Material	Iroko wood
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	II
Earth Leakage	0.1
Suitable for coastal areas	Yes (with appropriate treatment)
UK Building Regulations	N/A

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
BL03PIS27	Natural	Triple LED Pointed	5W	2700K	110°	156	31	78	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	NEW 1.5mm SY 2 Core PVC Steel Braid Cable, 2M Length.
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A

ACCESSORIES

BOL LED BRACKET	Stainless steel bracket for BOL LED range	Sold Separately
JB5	Gel filled junction box	Sold Separately

5W 5W at 350mA or 700mA

Coastal Protected

IP65 IP65 ideal for outdoor areas

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Choice of wood finishes: Iroko, Sapele or Oak

Pointed, Chamfered or Domed top

Choice of low-voltage or straight-to-mains

Side-entry cable or base-entry cable options

Three colour temperature options: 2700K, 3000K or 4000K

7 year warranty

BEAM ANGLE: **110°**

