





TRAFFIC ZONE. SEE PROTECTION MEASURE

In areas where traffic loading is expected, pipes laid at depths less than 0.9 metre below the finished surface of a road, (1.2m in adoptable situations) should be protected with a concrete slab of suitable strength which should bridge the full width of the trench so it sits on the trench wall.

Klargester BioDisc® Domestic Sewage Treatment Plant




The Klargester Domestic BioDisc® is engineered to treat wastewater to the highest level of standards and offers one of the lowest lifetime costs compared to other treatment processes.

- Product Benefits**
- Utilises Rotating Biological Contactor technology.
 - Low running costs.
 - Low level visibility with a lockable child-proof cover – safe for children and pets.
 - Delivers better than 95% pollution removal.
 - 10 year warranty options available when purchased with a service and maintenance plan.
 - Supplied with a control panel and alarm.
 - Managed Flow System.
 - Totally silent in operation.
 - The most stable process in the market.
 - Controls the discharge volume.

The Rotational Biological Contactor

The RBC is central to the operation of each Klargester BioDisc®. It supports a biologically active film or biomass onto which aerobic micro-organisms, naturally found in sewage, become established. Natural breakdown of sewage can then occur as described below.



01

Primary Settlement Tank

Wastewater and sewage flows into the primary settlement tank where the large solids are retained for future removal.

02

First Stage Biological Treatment

The liquor and fine solids then flow into the Biological Treatment Zone 1 where the first stage of treatment occurs.