

EPDM rubber roofing on 1mm thick external quality plywood on firing provide an manufactured resin joints by specialist company to 400°C. Provide 135mm thick calorific insulating battens joints with 5mm thick cellulose to v/s joints. finished with 125mm plied & 2400 stcm

EPDM rubber roofing on 19mm thick external quality plywood on lining joists on 220 x 47mm C16 grade flat roof joists @ 400c/c

Continuous 35w wide soffits
ventilation

Cementitious waterproofing consists slurry to outside face

SECTION A-A

SECTION B-B

PROPOSED FRONT ELEVATION

PROPOSED	SIDE	LEVATION
----------	------	----------

PROPOSED REAR ELEVATION

[illegible]

EXISTING SECTION A-A THROUGH FRONT GARDEN

New permeable block paving on sand blunder
hardcore 30mm thick

PROPOSED SECTION A-A THROUGH NEW HARSTANDING

PROPOSED GROUND FLOOR / SITE LAYOUT

New. Deep keeps

AMENDMENTS

16' Details of new handbraking added	1. Cellulose
15' Size of Extension Reduced	1. Cellulose

2006	PROPOSED SINGLE STOREY FLAT ROOF EXTENSIONS TO PROVIDE SELF CONTAINED UNIT					
	ADDRESS					
	ELLAND HOUSE, 12 FAIRVIEW ESTATE OLD WINCH FAIR ROAD, SWANSEA ROAD, M.T.					
	DEAR NO	SCALE	RATE	DEADW		
	20 of 2	1:50, 1:100		AUG 2012		
				DEC 2013		
				MARCH 2013		

SCAN + COPIES