

Specifications Table for 4MXM-A

					4MXM68A2V1B	4MXM80A2V1B (Archived)
Sound pressure level	Heating		Nom.	dBa	49	49
	Cooling		Nom.	dBa	48	48
Standard Accessories	Installation manual				1	1
	Screw bag				1	1
	Drain plug				1	1
	Reducer assembly				1	1
	Drain cap (1)				6	6
	Drain cap (2)				3	3
Refrigerant	GWP				675	675
	Charge			kg	2.00	2.40
	Type				R-32	R-32
Operation range	Cooling	Ambient	Max.	°CDB	46	46
			Min.	°CDB	-10	-10
Piping connections	Level difference	IU - IU	Max.	m	7.5	7.5
		IU - OU	Max.	m	15	15
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)

	Total piping length	System	Actual	m	60	70
Dimensions	Unit		Width	mm	974	974
			Depth	mm	408	408
			Height	mm	734	734
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor
Weight	Unit			kg	63	67
Power supply	Phase				1~	1~
	Frequency			Hz	50	50
	Voltage			V	220-240	220-240
Notes					(1) - For one room	(1) - For one room
					(2) - See separate drawing for operation range	(2) - See separate drawing for operation range
					(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data
					(4) - Contains fluorinated greenhouse gases	(4) - Contains fluorinated greenhouse gases